

MOTRAX 2T

2-STROKE ENGINE OIL

Description

Motorcycle Engine oil 2T Mineral is a high quality mineral lubricants suitable for use in air-cooled 2-stroke engines, in diverse applications. Three grades, called TSC-1, 2 or 3 are available. Depending on the grade, it can be used in different applications:

TSC-1: Suitable for mopeds, lawn mowers, small generators.

TSC-2: Suitable for motor scooters, motorcycles, chain saws (up to 32:1 fuel to oil ratio).

TSC-3: Suitable for motorcycles, snowmobiles, chain saws (above 32:1 fuel to oil ratio), water cooled engines not requiring NMMA TC-W oils.

Benefits

Our Motrax 2T reduces pre-ignition and plug fouling. It has excellent protection against piston seizure, ring sticking, engine deposits and exhaust blocking.



Performance levels

- API TA (TSC-1)
- API TB (TSC-2)
- API TC (TSC-3)
- JASO FB

Typical Properties

		TSC-1	TSC-2	TSC-3
Code		LUB004001	LUB004002	LUB004004
Density 15 °C	kg/m ³	885	887	889
Viscosity 40 °C	cSt	72.5	72.5	72.5
Viscosity 100 °C	cSt	9.1	9.1	9.1
Viscosity Index		108	108	108
Pour Point	°C	-25	-25	-25
Flash Point C.O.C	°C	230	230	230
TBN	Mg (KOH/g)	0.5	1.0	1.5
Operating Temperature	°C	-20/150	-20/150	-20/150